



ELASTOTET S.A.

SEALANTS • ADHESIVES • COATINGS • AEROSOLS  
ΣΦΡΑΓΙΣΤΙΚΑ • ΣΥΓΚΟΛΛΗΤΙΚΑ • ΣΤΕΓΑΝΩΤΙΚΑ • ΣΠΡΕΥ

# LASTOSPAT

Masonry acrylic putty for interior and exterior use.  
Packaging: 0.4 kg, 0.8kg, 5kg

## PHYSICAL & TECHNICAL PROPERTIES

**Colour:** White. After drying it can be painted

**Consumtion:** 2-3 m<sup>2</sup> per kilo

## APPLICATION FIELDS

LASTOSPAT is suitable for filling and coating of plaster or concrete. It is suitable for filling and coating of plaster or concrete. It has excellent working, filling and leveling properties. It dries fast without cracking and is easy to sand giving a smooth and durable surface without imperfections.

## APPLICATION INSTRUCTIONS

Surfaces must be clean, dry and free from all defective and poorly adhering material, dirt, grease and salts. Lastospat is applied without thinning by knife and it can be sanded after 3 hours using a suitable abrasive paper. It can be recoated with emulsion or solvent based paints.

Apply the material and let it dry at temperatures between 10oC and 35oC. Treatments such as sanding, welding, burning off, etc of paint films may generate hazardous dust and/or fumes. Work in well ventilated areas. Use suitable personal (respiratory) protective equipment, as necessary.

### Warning to users

The information contained in this document is given in good faith based on our current knowledge. It is only an indication and is in no way binding, particularly as regards infringement of or prejudice to third party rights through the use of our products. ELASTOTET GUARANTEES THAT ITS PRODUCTS COMPLY WITH ITS SALES SPECIFICATIONS. This information must on no account be used as a substitute for necessary prior tests which alone can ensure that a product is suitable for a given use. Users are responsible for ensuring compliance with local legislation and for obtaining the necessary certifications and authorisations. Users are requested to check that they are in possession of the latest version of this document and ELASTOTET is at their disposal to supply any additional information.