



Relief

Technical Specifications

Date of issue: 03/11/2015

Version Number: 7th

Special textured paint



RELIEF is a hard wearing texture coating that can be applied on every interior and exterior surface made of concrete, plaster, wood, hardboard, asbestos cement, bricks, etc. It provides a tough and flexible finish that gives long term protection against hard weather conditions and beauty that lasts. It has strong adhesion properties, covers completely any surface imperfections and can be used on every new or old surface, for decorative purposes.

Surface preparation

Ensure that the surface is in sound condition, dry, free from grease, dust, dirt, concrete salts and poorly adhesive materials. On new surfaces, apply one coat of RELIEF, thinned 15-20% with clean water. On previously painted or old surfaces, apply one coat of VERNILAC's primer DUROCOAT, thinned 75-100% with White Spirit.

Thinning

Thin 15-20% with clean water, only for surface priming purposes. As a topcoat, thin 0-15% with clean water.

Physical / Technical Characteristics

Viscosity	100±10 PS (20°C)
Density	1,7±0,017 kg/l (ISO 2811.01, 20°C)

Application

Stir thoroughly and occasionally during use. Apply one coat of RELIEF properly diluted, by using a special roller to achieve the desirable pattern on every new or repainted interior and exterior surface made of concrete, plaster, wood, hardboard, asbestos cement, bricks, etc. Do not apply when air and surface temperatures are below 5°C, above 40°C and/or humidity level is above 80%.

Drying

Drying times on a day of around 25°C: 2-6 hrs. Under cooler or humid conditions, allow longer times.

Coverage

1-2 m² per kilo approximately, on a properly prepared surface, depending on the desired surface texture.

Colour shades

Available in white and can be tinted by using the basic colours of SUPERPAL CLASSIC.

Storage

12 months, if stored in factory sealed containers, in a cool, dry place and temperatures ranging from 5°C to 40°C. Left over paint must be stored, in tightly sealed containers and temperatures ranging from 5°C to 40°C.

Clean up

Clean up tools and equipment with water, immediately after use. If needed, use soap or a household detergent solution. Do not empty waste water into drains or watercourses.

Volatile organic compounds (VOC)

The maximum EU limit value (Directive 2004/42/CE) for this product [Category A/a "Interior matt walls and ceilings (gloss <25@60°)", Type WB] is 30 g/l (2010). This product contains maximum 29 g/l VOC (ready for use).

Packaging

White	5 kg.	15 kg.
-------	-------	--------

Safety information

Read the label before use. For detailed instructions - precautions, consult the Product Safety Data Sheet. Poison Information Centre: (+30) 210 77 93 777.



All the information provided in this technical data sheet is the result of the scientific knowledge of the company's personnel and the practical experience in product application. This document doesn't express or imply a guarantee as the company cannot control and bears no responsibility for the conditions and the manner of application, the adjustment and the modification of the product when used by the customer. The customer must confirm by his own means that the product is suitable for the intended use. The current version of technical data sheet withdraws all previous versions for this product.